rything in nature.
Rajo-guṇa	The quaity of mobility or activity.

Rechaka	Exhalation, emptying of the lungs.
Ṛṣi	An inspired sage.
Ṙu	The second syllable in the word 'guru', meaning light.
Sādhaka	A seeker, an aspirant.
Sādhanā	Practice, quest.
Sādhana-pāda	The second part of Patañjāli's Yoga Sūtras, dealing with the means.
Sahajāvasthā	The natural state of the soul in samādhi.
Śalabha	A locust.
Sālamba	With support.
Sama	Same, equal, even, upright.
Sama-sthiti	Standing still and straight.
Samādhi	A state in which the aspirant is one with the object of his meditation, the Supreme Spirit pervading the universe, where there is a feeling of unutterable joy and peace.
Samādhi-pāda	The first part of Patañjali's Yoga Sūtras, dealing with the state of samādhi.
Samāna	One of the vital airs, whose function is to aid digestion.
Saṁśaya	Doubt.
Saṁskāra	Mental impression of the past.
Śankarāchārya	A celebrated teacher of the doctrine of Advaita.
Ṣaṇmukhī-mudrā	A sealing posture where the apertures in the head are closed and the mind is directed inwards to train it for meditation.
Santoṣa	Contentment.
Saraswatī	A tributary of the Ganges. Also the name of the goddess of speech and learning, the consort of Brahmā.
Sarva	All, whole.
Sarvāṅga	The whole body.
Satī	The daughter of Dakṣa Prajāpati. She immolated herself for the insult offered to her husband Śiva by her father, and was then reborn as the daughter of Himālaya and again won Siva as her husband. She was the mother of Kārtikeya (the god of war) and of Ganapati (the god of learning, wisdom and good luck).
Sattva	The illuminating, pure and good quality of everything in nature.
Sattva-guṇa	The quality of goodness and purity.
Śaucha	Purity, cleanliness.
Śava	A corpse, a dead body.
Setu	A bridge.
Setu-bandha	The construction of a bridge. Name of an āsana in which the body is arched.
Siddha	A sage, seer or prophet; also a semi-divine being of great purity and holiness.

Sirā	A tubular organ in the body. *See* nāḍī.
Śirṣa	The head.
Śiṣya	A pupil, a disciple.
Śiva	Name of the third god of the Hindu Trinity, who is entrusted with the task of destruction.
Śiva-saṁhitā	A classical textbook on Haṭha-yoga.
Smṛti	Memory, a code of law.
Śodhana	Purification, cleansing.
'Soham'	'He am I'; the unconscious repetitive prayer that goes on with every inhalation within every living creature throughout life.
Śoka	Anguish, distress, grief, sorrow.
Śraddhā	Faith, trust.
Steya	Theft, robbery.
Sthita-prajñā	One whose wisdom is firmly established and does not waver; one who is unmoved by the dualities of pleasure and pain, gain and loss, joy and sorrow, victory and defeat.
Sthiti	Stability.
Styāna	Languor, sloth.
Sukha	Happiness, delight, joy, pleasure, comfort.
Sumanasya	Benevolence.
Śunyāśūnya	The mind is in a state of void (Śūnya) and yet a state that is not void (aśūnya).
Supta	Sleeping.
Sūrya	The sun.
Sūrya-bhedana	Piercing or passing through (bhedana) the sun. Here the inhalation is done through the right nostril, from where the Piṅgalā-nāḍī or Sūrya-nāḍī starts. Exhalation is done through the left nostril, from where the Iḍā-nāḍī or Chandra-nāḍī starts.
Sūrya-nāḍī	The nāḍī of the sun. Another name for Piṅgalā-nāḍī.
Suṣumṇā	The main channel situated inside the spinal column.
Suṣupti-avasthā	The state of the mind in dreamless sleep.
Sva	One's own, innate, vital force, soul, self.
Svādhyāya	Education of the self by study of divine literature.
Śvāna	A dog.
Svapnāvasthā	The state of the mind in a dream.
Śvāsa	Inspiration.
Śvāsa-praśvāsa	Heaving and sighing.
Svātmārāma	The author of the Haṭha-yoga-pradīpikā, a classical textbook on Haṭha-yoga.
Tāḍa	A mountain.
Tamas	Darkness or ignorance, one of the three qualities or constituents of everything in nature.
Tamo-guṇa	The quality of darkness or ignorance.
Tan or *Tān*	To stretch, extend, lengthen out.

Tap — To burn, to blaze, to shine, to suffer pain, to be consumed by heat.

Tapas — A burning effort which involves purification, self-discipline and austerity.

'Tat twam asi' — 'Thou that art.' The realization of the real nature of man as being part of the divine, and of the divinity within himself, which liberates the human spirit from the confines of his body, mind, intellect and ego.

Tattva — The true or first principle, an element or primary substance. The real nature of the human soul or the material world and the Supreme Universal Spirit pervading the universe.

Tattva-jñāna — The knowledge of the true principle.

Tejas — Lustre, brilliance, majesty.

Ṭha — The second syllable of the word 'haṭha'. The first syllable 'ha' stands for the sun, while the second syllable 'ṭha' stands for the moon. The union of these two is Haṭha-yoga.

Tirieng — Horizontal, oblique, transverse, reverse and upside down.

Tri — Three.

Triaṅga — Three limbs.

Trikoṇa — A triangle.

Tṛṣṇā — Thirst, longing, desire.

Turīyāvasthā — The fourth state of the soul, combining yet transcending the other three states of waking, dreaming and sleeping state – the state of samādhi.

Ubhaya — Both.

Udāna — One of the vital airs which pervades the human body, filling it with vital energy. It dwells in the thoracic cavity and controls the intake of air and food.

Ugra — Formidable, powerful, noble.

Ujjāyi — A type of prāṇāyāma in which the lungs are fully expanded and the chest is puffed out.

Unmanī — The state of samādhi.

Upaniṣad — The word is derived from the prefixes 'upa' (near) and 'ni' (down), added to the root 'sad' (to sit). It means sitting down near a Guru to receive spiritual instruction. The Upanishads are the philosophical portion of the Vedas, the most ancient sacred literature of the Hindus, dealing with the nature of man and the universe and the union of the individual soul or self with the Universal Soul.

Upaviṣṭha — Seated.

Upekṣā — Disregard. Upekṣā is not only a feeling of disdain for a person who has fallen into vice or a feeling of

	indifference or superiority towards him. It is also a self-examination to find out how one would have behaved in like circumstances and also how far he is responsible for the state of the fallen one and to help him on to the right path.
Ūrdhva	Raised, elevated, tending upwards.
Ūrdhva-mukha	Face upwards.
Uṣṭra	A camel.
Ut	A particle, denoting intensity.
Uttāna	An intense stretch.
Utthita	Raised up, extended, stretched.
Vāchā	Speech.
Vāchika	Relating to speech, oral.
Vairāgya	Absence of worldly desires.
Vajra	A thunderbolt, the weapon of Indra.
Valli	A chapter of the Upanishads.
Vāma	The left side.
Vāsanā	A celebrated sage, author of several Vedic hymns.
Vāyu	The wind, the vital airs.
Veda	The sacred scriptures of the Hindus, revealed by the Supreme Being.
Vibhūti	Might, power, greatness.
Vibhūti-pāda	The third part of the Yoga Sūtras of Patañjāli, dealing with the powers that the yogi comes across in his quest.
Vidyā	Knowledge, learning, lore, science.
Vikalpa	Fancy, resting merely on verbal expression, without any factual basis.
Vikṣepa	Distraction, confusion, perplexity.
Vikṣipta	Agitated state of the mind.
Viloma	Against the hair, against the order of things. The particle 'vi' denotes negation or privation.
Viparyaya	A mistaken view, which is later observed to be such, after study.
Vīra	A hero, brave.
Vīrabhadra	A powerful hero created out of Śiva's matted hair.
Virochana	A demon prince, who was the son of Prahlāda and the father of Bali.
Vīrya	Vigour, strength, virility, enthusiasm.
Viṣama-vṛtti	Uneven or vehement movement while breathing.
Viṣṇu	The second deity of the Hindu trinity, entrusted with the preservation of the world.
Viśvāmitra	A celebrated sage.
Vitasti	A span.
Vṛkṣa	A tree.
Vṛt	To turn, to revolve, to roll on.

Vṛtti — A course of action, behaviour, mode of being, condition or mental state.

Vyādhi — Sickness, disease, illness.

Vyāna — One of the vital airs, which pervades the entire body and circulates the energy derived from food and breathing all over the body.

Yama — The god of death. Yama is also the first of the eight limbs or means of attaining yoga. Yamas are universal moral commandments or ethical disciplines transcending creeds, countries, age and time. The five mentioned by Patañjali are: non-violence, truth, non-stealing, continence and non-coveting.

Yoga — Union, communion. The word 'yoga' is derived from the root 'yuj' meaning to join, to yoke, to concentrate one's attention on. It is the union of our will to the will of God, a poise of the soul which enables one to look evenly at life in all its aspects. The chief aim of yoga is to teach the means by which the human soul may be completely united with the Supreme Spirit pervading the universe and thus secure absolution.

Yoga-mudrā — A posture.

Yoga Sūtra — The classical work on yoga by Patañjali. It consists of 185 terse aphorisms on yoga and it is divided into four parts dealing respectively with samādhi, the means by which yoga is attained, the powers the seeker comes across in his quest and the state of absolution.

Yogi or *Yogin* — One who follows the path of yoga.

Yoni-mudrā — Yoni means the womb or source and mudrā a seal. Yoni-mudrā is a sealing posture where the apertures of the head are closed and the aspirant's senses are directed within to enable him to find out the source of his being.

Yuga — An age.

Yuj — To join, to yoke, to use, to concentrate one's attention on.

Yukta — One who has attained communion with the Supreme Spirit pervading the universe.

International Addresses

Main Associations and Centres Worldwide

AUSTRALIA

BKS Iyengar Association of Australasia
1 Rickman Avenue
Mosman 2088
NSW

Bondi Junction School of Yoga
First Floor
2A Waverley Street
Bondi Junction
Sydney 2022
NSW

CANADA

BKS Iyengar Yoga Association
27–F Meadowlark Village
Edmonton
Alberta
T5R 5X4

Centre de Yoga Iyengar de Montreal
919 Mont-Royal Oest
Montreal
PQ H2J 1X3

BKS Iyengar Yoga Association
PO 65694, Station F
Vancouver, BC
V5N 5K7

Victoria Yoga Centre
3918 Olympic View Drive
RR4, Victoria, BC
V9B 5T8

BKS Iyengar Yoga Association of Ontario
c/o 85 Glenforest Road
Toronto, Ontario
M4N 2A1

FRANCE

Centre de Yoga Iyengar de Paris
also Association Francaise de Yoga Iyengar
35 ave Victor Hugo
75116 Paris

Centre de Yoga Iyengar de Lyon
Clos de Fourviere
40 Rue Roger Rodisson
69005 Lyon

Centre de Yoga Iyengar de Montpellier
5 bis Enclos Tissie Sarrus
34000 Montpellier

For classes in Marseille, Strasbourg, Toulouse, Nice, Tours, Grenoble, Nantes and Rouen, contact the Centre de Yoga Iyengar de Paris.

INDIA

R.I.M. Yoga Institute
1107 B/1 Shivajinagar
Pune 411 016

ITALY

Associazione Light on Yoga Italia
Via delle Route 49
50129 Firenze

JAPAN

Japanese Iyengar Yoga Association
Sembon Minami 557
Nishinari-Ku
Osaka Shi, Osaka Fu
Japan T557

HOLLAND

Iyengar Yoga Centre of Amsterdam
also Iyengar Yoga Association of Holland
8 Karthuizersdwars St
1015 KP Amsterdam

NEW ZEALAND

Information available from BKS Iyengar Association of Australasia (*see* Australia)

RUSSIA

Iyengar Yoga Centre of Moscow
c/o 16–49 Leninsky Prospect
Moscow 117 071

SOUTH AFRICA

BKS Iyengar Institute
58 Trelawney Road
Pietermaritzburg
Natal 3201

Iyengar Yoga Association of South Africa
PO Box 78648
Sandton 2146

SPAIN

EYI—Centro de Yoga Iyengar de Madrid
Carrera de San Jeronimo 16
5 28014
Madrid

Scola de Yoga
C—Hortes 2
17600 Figueres

UK

Manchester & District Institute of Iyengar Yoga
134 King Street
Dukinfield
Tameside
Greater Manchester

Edinburgh Iyengar Yoga Centre
195 Bruntsfield Place
Edinburgh EH10 4DQ

Contact the above for information about other local Institutes:

Birmingham Iyengar Yoga Institute
Bradford & District Institute of Iyengar Yoga
Bristol Iyengar Yoga Institute
Cambridge Iyengar Yoga Institute
Hampshire Iyengar Yoga Association
Light on Yoga Association
Liverpool & District Institute of Iyengar Yoga
North East Institute of Iyengar Yoga
Nottingham Iyengar Yoga Institute
Oxford Region Iyengar Yoga Group
South West Iyengar Yoga Institute
Sussex Iyengar Yoga Institute

USA

BKS Iyengar Yoga Institute of Los Angeles
also BKS Iyengar Yoga National Association of the United States, Incorporated
and Iyengar Yoga Association of Southern California
8223 W. Third Street
Los Angeles
CA 90038

Iyengar Yoga Institute of San Francisco
also Iyengar Yoga Association of Northern California
2404–27th Avenue
San Francisco
CA 94116

Ann Arbor 'Y' Iyengar Yoga
350 S 5th Avenue
Ann Arbor
MI 48014

Iyengar Yoga Institute of New York
also BKS Iyengar Yoga Association of Greater New York
27 W 24th Street
Suite 800
New York
NY 10011

Iyengar Yoga Association of Massachusetts, Inc.
240–A Elm Street
Somerville
MA 02114

Iyengar Yoga Association of Minnesota
Box 10381
Minneapolis
MN 55458–3381

Iyengar Yoga Assocaiation of Wisconsin
Route 2
Box 70E
La Crosse
WI 54601

Iyengar Yoga Association of the Midwest Bioregions
310 Gralake
Ann Arbor
MI 48103

Iyengar Yoga Association of Northern Michigan
2319 W. Midland Road
Auburn
MI 48611

THE 100 DEADLIEST KARATE MOVES

The Master Teacher The
Imperial Grand Potentate, Noble: Rev. Dr. Malachi Z. York 33°/720°.
Defines Success"

QUESTION: What is Success?

ANSWER: Success is the progressive realization of a worthy idea. If you have a goal and you are working towards that goal, then you're on the path to success.

"A 30 Day Program "

All One Has to Do Is Apply The Method To Their Life And Your Life Will Never Be The Same Again!

~~~
~~~

I create positive habits.

I always think positive.

I take control of my mind.

My mind will only think of what I allow it to think.

I Do more.

I think more.
I give myself more then I ever did before.

I don't worry about how I am going to achieve my goals.

All The answers will come to me.

I think of all the reasons I can be successful.

I write out the persons that I love to become

I am like _____
I can not live no other way after this right knowledge.

I my whole life to live in a superior way.

I am super-strong mentally.

I am a super-strong physical .

I am super-strong 9 Ethereally

I am cured of all mental diseases, namely ignorance.

I am a Supreme Being of the pure radiant Green Light.

I change my mental environment and I change my life.

I am a superior thinker.

I am bred to be superior in mind.

I am programmed by my superior mental environment

I am educated In a Superior mental environment.

Named Nuwaubu/Wu-Nuwaubu

I am physically and spiritually free.

I am a supreme being.

I am goal-minded.

I achieve anything I want to achieve in my life.

I am financially independent.

I know how to use my superior knowledge to become super-successful.

I get everything I want in my life.

I have the super-magic touch.

Anything I touch turns Into success.

I continue to become more & more successful in my life.

I always think big and successful.

I am a super-successful supreme being.

I am progressive In the realization of my worthy ideas.

I do everything in any field I choose to.
I am successful in anything I choose to do, because that's what I want to do.

I propagate the 'Message of the Most High'.

I set goals.

I am going to ....(state action)_____.

I am going to ....(state action)_____.

I am going to ....(state action) _____

(set date for deadline).

_____

I will succeed.

I will reach all of the goals that I set for myself.

I set out to achieve all of them.

I want to become a "Supreme Being "

I am a "Supreme Being "

Success is anybody that's doing a pre-determined job.

I will (state action)_____.

I am (Determine)_____.

I posses a burning desire to be what I think about all the time.

I create all my opportunities in my life.

I know where I am going.
I have complete plans.
I know my directions.
I know my destination.
I know where I am going all the time.
I have the superior guidance.

I am a superior sales man.
I have no limits in ALL

I always achieve.
I sell anything, because I want to.
I sell everything.
I believe in what I am selling.

I don't hurt anybody.

I don't displease anybody.

I make everything I do marketable to all.

I am superior competitor.
I am a super-winner.
I super-succeed in my life.
I really overstand this principle completely.

My life is altered for super-success

The Bes things are always attracted to me.

Everything I want, I get.

From now on, I won't have any problems.

I won't have any worries.

I don't have any doubt, nor any fears in my life.

~~~~~~
"THIS IS THE KEY!!"
SAY This for 30 days straight

I am what I think about all the time.

(say what you want to think about All the time)

<<<here>>>

_____ _____

Everything will come if I only be patient and wait for it.

I am completing my purpose.

I alter my life for The Bes.

I alter my attitude to a superior state of mind.

I am a superior mind.

I care enough for super results.

I will achieve it.

I achieve all

I am super-rich.
I am super wealthy
I am super-healthy.
I am super-intelligent.
I am super- knowledgeable on all subjects on earth and the whole boundless universe.
~~~~~~

Anything I think in my mind, I am it.
Anything I feel in my heart I am it.

My life is what my thoughts make it.

I posses positive, crystal clear and vivid pictures in my mind of what I want to do.

I posses positive, crystal clear and vivid pictures in my mind of what I want to become

I know my goals and purposes In my life.

I have set a target before me.

I am prepared.

I practice.

I am talented.

I am skillful.

I have the complete idea.

I achieve all of my goals when I think about them.

I am helping to save positive agreeable Nubian people

who don't believe in themselves.

Possible Nine-mind revision:
(I am helping to save positive agreeable Nubian people who don't KNOW themselves.)

I totally believe in myself.

Possible Nine-mind revision:
(I totally trust in my abilities within myself.)

I will instill this superior mind-concept in all of my children.

I am the greatest of the great.

My children are the greatest of the great.

I am a chosen child of Anu.

I have the superior-faith

I have super-determination.

I will succeed.

I succeed

I know all things are possible to me.

I think in only positive terms.
I get only positive things sent to me.

I believe and I succeed.

Possible Nine-mind revision:
(I am conscious of my ability to achieve success)

I know and I succeed.

I have no doubt in myself.

I attempt all things I want & wish for.

I make everything happen for me in my life

I become what I think about.

I think about positive, concrete, worth-while goals and ideas.

I will always become what I think about.

I think about all the positive things I want to become in my life.

I become what I think about.

Anything I plant in my mind I become it.

I plant super-success in my mind and everything I want and wish for in my life becomes reality.

I concrete on only worth-while goals.

I always value my mind, my body, my soul and my spirit.

I don't take my mind, my body, my soul and my spirit for granted.

I plan my goals in my mind.

I am making the most important decision in my life.

I plan all my goals in my mind and I achieve them.

I picture myself as a Supreme Being.

I see myself as having already achieving all goals in my life.

I am outstanding in everybody's eyes.

I am a great, supreme being.

I find everything I need in my life to help all others.

I am super-rich in personality, fame and respect.

I plant any thought In my mind and I easily achieve it.

I care and work towards achieving my goals in life and everything

I plant in my mind becomes a reality.

That is Universal law.

This always works, because this is Universal law.

I am where I want to be.

I am guided by my Inner Being

I think, I think and I think

I am learnt in this superior science.

I overstand this Supreme science.

I know this supreme science works with the forces of nature

put your want and wish in the lines

I am _____.

I believe in_____.

Possible Nine-mind revision:
(I focus on) _____.

I have faith in_____.

Possible Nine-mind revision:
(I strive towards) _____.

I am in control of_____.

I do the job that I love doing.

I only do super-great things in my life

I am A Supreme Being of the pure radiant GREEN LIGHT